

RP-110

RP-110**Desktop POS Printer**

project based available
in white housing

FEATURES

- Simple and sleek design
- High performance easy maintenance
- Wheel-type paper jam control
- High speed printing at 250mm/sec(9.8ips)
- Visible wireless (project based BT/ WiFi version) connectivity status
- Ideal for front exit printing, mounted with wall mount keyholes
- Simple and easy service on components including head, motor, cutter, PCB, etc

RP-110

Specifications

	RP-110
Color	Black/White
Printing technology	Thermal direct
Print speed	up to 250mm/s
Paper type	Thermal receipt paper/black mark supported
Paper roll	Media width max. 80mm (3.14"), maximum outer diameter Ø83mm (3.2")
Paper roll core	12.5mm ± 0.5mm
Paper thickness	0.06-0.08mm
Print width	72±0.5mm
Paper path	Paper out up or front
Print density	576 points per row or 512 points per row
Dot Pitch	0.125mm x 0.125mm
Characters per line (CPL)	Font A (12x24) - 48 columns / 42 columns Font B (9x17) - 64 columns / 56 columns
Resolution	203 DPI
Line space	3.75mm (adjustable by command)
Print command	Compatible with ESC/POS commands
Interface type	Standard: USB(B type)+Serial(RS- 232C_9pin)+Ethernet Built-in Option (project based): Bluetooth Smart Ready(Bluetooth5.0+BLE) or WiFi(802.11 a/b/g/n)
Character size	ANK character, Font A: 1.5mm×3.0mm (12×24 points) Font B: 1.1mm×2.1mm (9×17 points) Simplified/complex font: 3.0mm×3.0mm (24×24 points)
Figure	Monochrome BMP and other image files can be downloaded to FLASH
Bar-code type	1D: EAN-8, EAN-13, Code 39, Code 93, Code 128, ITF, UPC-A, UPC-E, Codabar
QR code	QR Code, PDF41
Emulation	ESC/POS Command compatible
Driver	Windows Driver(XP ~, Server2003 ~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver Android SDK, iOS SDK, Windows SDK
Extended character list	PC437(Std.Europe), (Katakana), PC850(Multilingual), PC860(Portugal), PC863(Canadian), PC865(Nordic), (West Europe), (Greek), (Hebrew), (East Europe), (Iran), (WPC1252), PC866(Cyrillic#2), PC852(Latin2), (PC858) , (IranII), (Latvian), (Arabic), (PT1511251)

RP-110



Specifications

	RP-110
Reliability MCBF	80 million lines
Reliability TPH Life	150Km
Sensor	Paper end, Cover open
Cutter Type	Guillotine
Cutter Life	1,500,000 cuts
Cutter method	partial/full cut
sensor	paper end/ cover open/ black mark
Input buffer	128Kbytes
NV Flash	256Kbytes
Power adapter voltage input	AC 100-240V/50~60Hz
Power adapter voltage output	DC 24V/2.5A
Cash-box/drawer control	DC 24V/1A
Working environment	Temperature: 0°C ~45°C; humidity: 10%~80% (non-condensate)
Storage environment	Temperature: -10~60°C; humidity: 10~90%
Operating system	Windows Driver(XP ~, Server2003 ~), Linux Driver, Mac Driver, OPOS Drive
Size	174*136*132mm(L*W*H)
Net weight	1.04kg

Contact Now

Europe +49 40 450 635-0
United Kingdom +44 1928 579 707
Spain +34 913 120632
Slovenia +386 1 566 25 20
Poland +48 22 115 93 82

info@partner-tech.eu
sales-uk@partner-tech.eu
comercial@partner-tech.eu
prodaja@partner-tech.eu
officepoland@partner-tech.eu