

TS-210

THEMIS

TS-210

Scanner Solution



Specifications

	TS-210		
Image Size	1280 x 800 pixels		
Reading Indicator	Beeper, LED		
Scanning Angle	± 70°, ± 75°, 360° (Skew, Pitch, Roll)		
Depth of Field	HD		SR
	3 mil Code39 (3 chars)	25 mm - 50 mm	/
	4 mil Code39 (9 chars)	10 mm - 90 mm	30 mm - 90 mm
	5 mil Code39 (3 chars)	5 mm - 115 mm	20 mm - 120 mm
	13 mil UPC (6 chars)	0 mm - 250 mm	0 mm - 280 mm
	20 mil Code39 (1 char)	15 mm - 340 mm	15 mm - 430 mm
	6.7 mil PD417 (20 chars)	10 mm - 100 mm	15 mm - 120 mm
	10 mil QR (20 chars)	0 mm - 155 mm	0 mm - 165 mm
	10 mil DM (20 chars)	0 mm - 160 mm	0 mm - 165 mm
	20 mil QR (20 chars)	0 mm - 270 mm	0 mm - 340 mm
Barcode Types	1D	2D	
	UPC-A, UPC-E, UPC-E1, EAN-13, EAN-8, ISBN (Bookland EAN), ISSN, Code 39, Code 39 full ASCII, Code 32, Trioptic Code 39, Interleaved 2 of 5, Industrial 2 of 5 (Discrete 2 of 5), Matrix 2 of 5, Codabar (NW7), Code 128, UCC/EAN 128 (GS1-128), ISBT 128, Code 93, Code 11 (USD-8) MSI/Plessey, UK/Plessey, China Post, China Finance, GS1 DataBar (formerly RSS) variants	PDF417, MicroPDF417, QR Code, MicroQR Code, DataMatrix, Han Xin Code, Aztec Code	
Humidity	5% ~ 95%		
Drop Resitance	yes		

Specifications

	TS-210
Color	black, grey
Certification	CE, LVD, IP52
Input Voltage	DC 5 +/- 0.25 V
Amperage	Working: 300mA (Max: 480mA), Standby: 160mA
I/O Interfaces	RS-232, USB Keyboard, USB virtual COM
Cable	2m straight, RJ45 connector, field replaceable
Weight	132 g (without cable)
Operat. Temperature	0°C ~ 50°C
Storage Temperature	-40°C ~ 60°C
Dimensions (WxHxD)	63 x 153 x 90 mm
Light Source	Illumination : 5000 K , white LED Aiming: 525 nm peak wavelength, green LED
Optional Accessories	RS232 cable with 5V adaptor, Stand

Contact Now

Europe	+49 40 450 635-0
United Kingdom	+44 1928 579 707
Spain	+34 913 120632
Slovenia	+386 1 566 25 20
Poland	+48 22 115 93 82
France	
South Africa	+27 87 094 0355

info@partner-tech.eu
sales-uk@partner-tech.eu
comercial@partner-tech.eu
prodaja@partner-tech.eu
officepoland@partner-tech.eu
ptf-contact@partner-tech.eu
PTSAInfo@partner-tech.eu